

# USG OLYMPIA™ MICRO™ ACOUSTICAL PANELS

CLIMAPLUS™ PERFORMANCE

USG Olympia™ Micro™ Acoustical Panels with ClimaPlus™ Performance, and USG Donn® Brand Identitee® DXI™ Acoustical Suspension System

TO ORDER SAMPLES, GO TO [USG.COM](http://USG.COM) OR [CGCINC.COM](http://CGCINC.COM)



Flat White  
050

## FEATURES AND BENEFITS

- Nondirectional pattern reduces installation time and waste.
- Economical, fine-textured panel.
- Excellent light-reflective finish (LR-0.86) reduces light fixtures and energy use.
- USDA Certified Biobased Product.<sup>7</sup>
- ClimaPlus™ 30-year limited system warranty against visible sag, mold and mildew.

## APPLICATIONS

- Offices
- Classrooms
- Reception/lobby areas
- Hotels
- Conference areas
- Retail stores

## SUBSTRATE

- Wet-formed mineral fiber

Fine-Textured Panel

# USG OLYMPIA™ MICRO™ ACOUSTICAL PANELS

## CLIMAPLUS™ PERFORMANCE


ORDER SAMPLES/LITERATURE  
 USG: usg.com or samplitt@usg.com  
 CGC: contact Sales Representative

TECHNICAL SERVICES  
 800.USG.4YOU (874-4968)

FOR MOST UP-TO-DATE  
 TECHNICAL INFORMATION  
 AND LEED REPORT TOOL  
 usgdesignstudio.com  
 cgcdesignstudio.com



PRODUCT CERTIFIED  
 FOR LOW CHEMICAL  
 EMISSIONS:  
 UL/COM/GG  
 UL 2818



### USG OLYMPIA™ MICRO™ PANELS UNPERFORATED<sup>9</sup>

### USG OLYMPIA™ MICRO™ PANELS 50 NRC<sup>6</sup>

### USG OLYMPIA™ MICRO™ PANELS 60 NRC<sup>6</sup>

### USG OLYMPIA™ MICRO™ ILLUSION™ TWO/24 PANELS

#### PATTERNS

Edge	Panel Size	Fire Rating	Item No.	UL Classified			Color	Grid Options	VOC Emissions	Anti-Mold & Mildew	Recycled Content <sup>1</sup>	Panel Cost
				NRC	CAC Min.	LR <sup>2</sup>						
SQ	2'x2'x5/8"	Class A	4210	—	35	0.86	White	A,B,C	Low		41%	\$\$
	2'x4'x5/8"		4913	—	35	0.86	White	A,B	Low		41%	\$\$
SQ	2'x2'x5/8"	Class A	4211	0.50	30	0.86	White	A,B,C	Low		41%	\$\$
	2'x4'x5/8"		4411	0.50	30	0.86	White	A,B	Low		41%	\$\$
SLT	2'x2'x5/8"	Class A	4221	0.50	35	0.86	White	D	Low		41%	\$\$
	2'x4'x5/8"		4421	0.50	35	0.86	White	D	Low		41%	\$\$
FLB	2'x2'x5/8"	Class A	4231	0.50	35	0.86	White	E,F,G,H	Low		41%	\$\$
	2'x4'x5/8"		4431	0.50	35	0.86	White	E,F,G,H	Low		41%	\$\$
SQ	2'x2'x3/4"	Class A	4750	0.60	33	0.86	White	A,B,C	Low		58%	\$\$
	2'x4'x3/4"		4751	0.60	33	0.86	White	A,B	Low		58%	\$\$
SLT	2'x2'x3/4"	Class A	4752	0.60	35	0.86	White	D	Low		58%	\$\$
	2'x4'x3/4"		4753	0.60	35	0.86	White	D	Low		58%	\$\$
FLB	2'x2'x3/4"	Class A	4754	0.60	35	0.86	White	E,F,G,H	Low		58%	\$\$
	2'x4'x3/4"		4755	0.60	35	0.86	White	E,F,G,H	Low		58%	\$\$
SLT <sup>4</sup>	2'x4'x3/4"	Class A	4742	0.50	35	0.86	White	D	Low		58%	\$\$
ILT <sup>5</sup>	2'x4'x3/4"	Class A	4744	0.50	35	0.86	White	I	Low		58%	\$\$

#### USG Illusion™ Two/24



The look of 2'x2' panels

#### Low Emissions (VOC)

Third party (GREENGUARD Gold) certified for low-emitting performance, meets California Department of Public Health's (CDPH) Standard Method v1.2 - 2017 (CA Section 01350). \*Certificates of Compliance\* for Low VOC Emissions are available on usg.com and at spot.ul.com.

#### ClimaPlus™ Warranty Performance<sup>3</sup>

Contains a broad-spectrum antimicrobial additive on the face and back of the panel that provides resistance against the growth of mold and mildew. Includes sag-resistance performance.

#### High Recycled Content

USG classifies High Recycled Content as greater than 50%. Total recycled content is based on product composition of postconsumer and preconsumer (postindustrial) recycled content per FTC guidelines.

#### GRID PROFILE OPTIONS

A USG DX*	B USG DXW™	C <sup>8</sup> USG Centricitee™ DXT™	D USG DX*	E USG Centricitee™ DXT™	F USG Identitee™ DXI™	G USG Fineline™ DXF™	H USG Fineline™ 1/8 DXFF™	I USG Centricitee™ DXT™

#### PHYSICAL DATA/ FOOTNOTES

**Product literature**  
 Data sheet: SC2180

**ASTM E1264 classification**  
 ASTM E1264-22 Type III, Form 2, Pattern C & E  
 ASTM E1264-23 Type A, Form A1.2, Pattern C & E

**ASTM E84 and CAN/ULC S102 surface-burning characteristics**  
 Class A  
 Flame spread: 25 or less  
 Smoke developed: 50 or less

**Online tools**  
 usgdesignstudio.com or cgcdesignstudio.com

**Weight**  
 0.775-0.993 lb./sq. ft.

**Thermal resistance**  
 R-1.4 (5/8" panels)  
 R-1.7 (3/4" panels)

**Maximum backloading**  
 See USG 30-Year Limited System Warranty Commercial Applications (SC2102).

**Maintenance**  
 Can be cleaned easily with a soft brush or vacuum.

#### Notes

- For details, see USG Sustainability tool at usgdesignstudio.com or cgcdesignstudio.com.
- LR values are shown as averages.
- For details, see USG 30-Year Limited System Warranty Commercial Applications (SC2102).
- Panels have 15/16" routing.
- Panels have 9/16" routing.

6. Mixing 0.50 and 0.60 NRC panels in the same ceiling plane is not recommended.

7. This product has achieved both BioPreferred initiatives: Federal Procurement Preference and Certified Product Labeling. See the complete listing of all USG ceiling panels on biopreferred.gov website.

8. Maximum 2'x2' with SQ edge panels.

9. Item numbers 4210 and 4913 are not UL Classified for acoustics.

#### Notice

The information in this document is subject to change without notice. CGC Inc. or USG Corp. assumes no responsibility for any errors that may inadvertently appear in this document.

SC2180/rev. 8-23  
 © 2023 USG Corporation and/or its affiliates. All rights reserved.  
 Printed in USA

Manufactured by  
 USG Interiors, LLC  
 550 West Adams Street  
 Chicago, IL 60661

The trademarks USG, CGC, CENTRICITEE, CLIMAPLUS, DONN, DX, DXF, DXFF, DXI, DXT, DXW, FINELINE, IDENTITEE, ILLUSION, MICRO, OLYMPIA, IT'S YOUR WORLD. BUILD IT., the USG/CGC logo, the design elements and colors, and related marks are trademarks of USG Corporation or its affiliates.

Safety First! Follow good safety/industrial hygiene practices during installation. Wear appropriate personal protective equipment. Read SDS and literature before specification and installation.

